



## DRYER

FOR VENDED LAUNDRY APPLICATIONS

INDUSTRIAL  
BY DESIGN

### Dependable & Efficient

---

- Superior Airflow
  - » Fast-drying results with advanced airflow pattern
- Large Capacity
  - » Large 7.0 ct. ft. cylinder
- Time Savings
  - » Large, easy-clean lint filter is located upfront

### Control

---

- Micro-Display
  - » Digital display shows vend price
  - » Four cycle options
  - » Cycle time countdown
  - » LED progress indicators
- Electromechanical
  - » Easy operation
  - » Basic temperature and fabric selections

### Activations

---

- Coin Drop Installed
- Prepped for Card Option on MDC
- Coin Slide on Electromechanical



# DRYER

Specifications	Front Control	Rear Control
Available Controls	MDC	MDC, Coin Slide
Capacity - lb (kg)	18 (8.2)	18 (8.2)
Cylinder Volume - cu. Ft. (liters)	7.0 (198)	7.0 (198)
Width - in (mm)	26 7/8 (683)	26 7/8 (683)
Depth - in (mm)	28 (711)	28 (711)
Height - in (mm)	44 3/8 (1126)	43 (1092)
Motor Size - HP (kw)	1/3 (0.25)	1/3 (0.25)
Available Heat Sources	Gas or Electric	Gas or Electric
Available Heating Element (Electric W)	4750 @ 208V 5350 @ 240V	4750 @ 208V 5350 @ 240V
Gas Inlet Connection - in (mm)	3/8 (9.5)	3/8 (9.5)
Gas Consumption - BTU/Hr	25,000	25,000
Exhaust Outlet Diameter - in (mm)	4 (102)	4 (102)
Exhaust Airflow - cfm (liters/sec)	220 (105)	220 (105)
Available Cycles*	High, Medium, Low, Delicates	High, Medium, Low, Delicates
Cycle Indicator Lights	Yes	Yes
Cylinder Finish	Galvanized	Galvanized
Available Colors	White, Stainless Steel	White
Door Type (Solid/Window)	Solid	Solid
Available Electrical Requirements - (Voltage/Hz/Ph)	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp
Net Weight - lb (kg)	Elec/Gas 150/155 (68/70)	Elec/Gas 135/140 (61/64)
Shipping Weight - lb (kg)	Elec/Gas 160/165 (73/75)	Elec/Gas 145/150 (66/68)
Shipping Dimensions		
Width - in (mm)	29 (737)	29 (737)
Depth - in (mm)	32 3/4 (832)	32 3/4 (832)
Height - in (mm)	45 1/2 (1156)	45 1/2 (1156)
Available Agency Approvals	Elec: cUL <sub>US</sub> , Gas: cCSA <sub>US</sub>	Elec: cUL <sub>US</sub> , Gas: cCSA <sub>US</sub>

ADA Compliant

\* Information shown applies to highest end control available

Note: Not all options are available for all models. Refer to the price list for the available models and options.



For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

©Copyright 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC  
Shepard Street  
Ripon, WI 54971